
Watershed Monitoring Program Comparison Kirsten Gallo - AREMP

PIBO EMAP AREMP



Program Objectives

- ❖ PIBO effects of management activity on aquatic and riparian communities in the range of PACFISH/INFISH and bull trout within the interior Columbia Basin
- EMAP monitor and assess the status and trends of national ecological resources
- AREMP effectiveness of Northwest Forest Plan on restoring and maintaining good watershed condition

Study Design


- PIBO random selection of 6th field HUCs stratified by ecoregion and management level
- *AREMP random selection of 250 6th field HUCs within NWFP area
- *EMAP random selection of sample sites

Watershed Selection

- Generalized Random Tessellation Stratified design
- developed by EPA
- * random selection of site locations
- sample is spatially balanced across resource

Watershed Selection Constraints

	PIBO	EMAP	AREMP
Land Ownership	≥ 50 % Federal	None	≥ 25 % Federal
Gradient	< 3%	None	None



PIBO

- ♦ 6th field HUCs
- 1 sample site per watershed
- lowest-most nonconstrained reach



AREMP


- 6th field HUCs
- multiple randomly-selected sites per watershed
- Sites selected using GRTS



EMAP

- Randomlyselected sites
- Watersheds delineated above site
- 1 site per watershed

Comparison of watershed areas



Site Layout

	PIBO	EMAP	AREMP
Reach length	20x BF	40x wetted	20x BF
Minimum length	80 m	150 m	150 m

Common Indicators

	PIBO	EMAP	AREMP
BF Width, Depth	X	X	X
Entrenchment	X	X	X
Sinuosity	X	X	X
Slope	X	X	X

Common Indicators


	PIBO	EMAP	AREMP
Substrate	X	X	X
Large Wood	X	X	X
Pools	X	X	X
Pool Depth	X	X	X

Biological Indicators

	PIBO	EMAP	AREMP
Periphyton	X	X	X
Invertebrates	X	X	X
Amphibians			X
Fish		X	X

Protocol Focus

- Slope
- * Bankfull width
- Percent pools
- ❖ Substrate D₅₀



Slope

- * PIBO & EMAP water surface
- *AREMP stream bed surface



Bankfull Width

- PIBO measured at 4 cross sections, located in the widest point in the first 4 riffles
- *EMAP measured at 11 equallyspaced cross sections
- AREMP measured at 6 or 11 equallyspaced cross sections

Percent Pools

- ❖ PIBO pools must be more than half wetted channel and include thalweg, and be longer than wide, maximum depth > 1.5x tail crest depth
- EMAP & AREMP pools must span wetted channel and be longer than wide

Substrate D₅₀

- PIBO measure 25 pebbles in each of the first 4 riffles
- EMAP measure 5 pebbles at 21 equally-spaced transects
- AREMP measure 11 pebbles at 11 equally-spaced transects

Summary

- All programs are designed to assess effects of management on resources.
- In general, protocols are very similar between programs.
- Need to assess whether data collected by each program differs predictably.